

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 30

SDS No.: 693565 V003.0

Revision: 12.07.2024

printing date: 18.09.2024

Replaces version from: 17.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3D PRO476 Black

LOCTITE 3D PRO476 Black UFI: AFXT-TVEE-E20P-D6C5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: 3D Printing Resin

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Toxic to reproduction Category 1B
H360F May damage fertility.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 2 of 30

V003.0



Contains 2-Hydroxyethyl methacrylate

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl

bismethacrylate

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide Reaction mass of pentamethyl-4-piperidylsebacates 2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester

Triacrylate ester Ethylene dimethacrylate

Signal word:	Danger
Hazard statement:	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H360F May damage fertility.
	H411 Toxic to aquatic life with long lasting effects.
Supplemental information	Restricted to professional users.
•	
Precautionary statement:	P201 Obtain special instructions before use.
Prevention	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing.
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P308+P313 IF exposed or concerned: Get medical advice/attention.
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
	P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LOCTITE 3D PRO476 Black Page 3 of 30

V003.0

SDS No.: 693565

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
EC Number REACH-Reg No.				
2-Hydroxyethyl methacrylate 868-77-9 212-782-2 01-2119490169-29	25- < 50 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319		
7,7,9(or 7,9,9)-trimethyl-4,13- dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate 72869-86-4 276-957-5 01-2120751202-68	10- < 20 %	Skin Sens. 1B, H317 Aquatic Chronic 2, H411		
Isobornyl methacrylate 7534-94-3 231-403-1 01-2119886505-27	5- < 10 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412	STOT SE 3; H335; C >= 10 %	
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8 278-355-8 01-2119972295-29	1- < 3 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317 Repr. 1B, H360Fd		SVHC
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5 915-687-0 01-2119491304-40	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Repr. 2, H361f	M acute = 1 M chronic = 1 ===== dermal:ATE = 3.171 mg/kg	
2-Propenoic acid, 2-methyl-, 2- (2-hydroxyethoxy)ethyl ester 2351-43-1	0,1-< 1 %	Eye Irrit. 2, H319 Skin Sens. 1, H317		
Triacrylate ester 52408-84-1 500-114-5 500-114-5 01-2119487948-12	0,1-< 1 %	Eye Irrit. 2, H319 Skin Sens. 1B, H317		
Butyl hydroxytoluene 128-37-0 204-881-4 01-2119565113-46	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
methacrylic acid 79-41-4 201-204-4 01-2119463884-26	0,1-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	STOT SE 3; H335; C >= 1 % ====== dermal:ATE = 500 mg/kg inhalation:ATE = 3,19 mg/l;dust/mist	
Ethylene dimethacrylate 97-90-5 202-617-2	0,1-< 1 %	STOT SE 3, H335 Skin Sens. 1, H317 Aquatic Chronic 3, H412	STOT SE 3; H335; C >= 10 % ====== dermal:ATE = > 5.000 mg/kg	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the $\rm H$ - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 4 of 30

V003.0

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 5 of 30

V003.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed. Refer to Technical Data Sheet.

7.3. Specific end use(s)

3D Printing Resin

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 6 of 30

V003.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DI-TERT-BUTYL-P-CRESOL]		10	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DITERTIARY-BUTYL-PARA- CRESOL]		2	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

LOCTITE 3D PRO476 Black Page 7 of 30

V003.0

SDS No.: 693565

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sewage treatment plant (STP)		10 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)		1 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Soil				0,476 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Predator						no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Marine water - intermittent		1 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	aqua (freshwater)		0,01 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	aqua (intermittent releases)		0,1 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	aqua (marine water)		0,001 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	sewage treatment plant (STP)		3,61 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	sediment (freshwater)				4,56 mg/kg		
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	sediment (marine water)				0,46 mg/kg		
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	Soil				0,91 mg/kg		
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	Predator						no potential for bioaccumulation
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (freshwater)		4,66 µg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Soil				0,118 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sewage treatment plant (STP)		2,45 mg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sediment (freshwater)				0,604 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (intermittent releases)		0,0179 mg/l				

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 8 of 30

V003.0

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl	aqua (marine	0.000466	1 1	
methacrylate	water)	mg/l		
7534-94-3 Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl	sediment		0,06 mg/kg	
methacrylate	(marine water)		0,00 mg/kg	
7534-94-3 Diphenyl(2,4,6-trimethylbenzoyl)phosphine	aqua	0,0014		
oxide	(freshwater)	mg/l		
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine	aqua (marine	0.00014		
oxide 75980-60-8	water)	mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	Freshwater -	0,014 mg/l		
oxide 75980-60-8	intermittent			
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	Marine water -	0,0014		
oxide 75980-60-8	intermittent	mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	sediment		0,115	
oxide 75980-60-8	(freshwater)		mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	sediment		0,0115	
oxide 75980-60-8	(marine water)		mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	Soil		0,0222	
oxide 75980-60-8			mg/kg	
Reaction mass of pentamethyl-4-	aqua	0,002 mg/l		
piperidylsebacates 1065336-91-5	(freshwater)			
Reaction mass of pentamethyl-4-	aqua (marine	0,00022		
piperidylsebacates 1065336-91-5	water)	mg/l		
Reaction mass of pentamethyl-4-	Freshwater -	0,009 mg/l		
piperidylsebacates	intermittent			
1065336-91-5 Reaction mass of pentamethyl-4-	sewage	1 mg/l		
piperidylsebacates	treatment plant	1 8		
1065336-91-5 Reaction mass of pentamethyl-4-	(STP) sediment		1,05 mg/kg	
piperidylsebacates	(freshwater)		1,03 mg/kg	
Reaction mass of pentamethyl-4-	sediment		0,11 mg/kg	
piperidylsebacates 1065336-91-5	(marine water)		0,11 mg/kg	
Reaction mass of pentamethyl-4-	Soil		0,21 mg/kg	
piperidylsebacates 1065336-91-5				
Reaction mass of pentamethyl-4-	Predator			no potential for
piperidylsebacates 1065336-91-5				bioaccumulation
Glycerol, propoxylated, esters with acrylic	aqua	0,006 mg/l		
acid 1-6.5PO 52408-84-1	(freshwater)			
Glycerol, propoxylated, esters with acrylic	aqua	0,057 mg/l		
acid 1-6.5PO 52408-84-1	(intermittent releases)			
Glycerol, propoxylated, esters with acrylic	Sewage	10 mg/l		
acid 1-6.5PO 52408-84-1	treatment plant			
Glycerol, propoxylated, esters with acrylic	sediment		0,078	
acid 1-6.5PO 52408-84-1	(freshwater)		mg/kg	
Glycerol, propoxylated, esters with acrylic	sediment		0,008	
acid 1-6.5PO 52408-84-1	(marine water)		mg/kg	
Glycerol, propoxylated, esters with acrylic	aqua (marine	0,001 mg/l		
acid 1-6.5PO 52408-84-1	water)			
Glycerol, propoxylated, esters with acrylic	Soil		0,012	
acid 1-6.5PO 52408-84-1			mg/kg	
2,6-Di-tert-butyl-p-cresol	aqua	0,000199		

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 9 of 30

V003.0

128-37-0	(freshwater)	mg/l		
2,6-Di-tert-butyl-p-cresol	aqua (marine	0,00002		
128-37-0	water)	mg/l		
2,6-Di-tert-butyl-p-cresol	sewage	0,17 mg/l		
128-37-0	treatment plant (STP)			
2,6-Di-tert-butyl-p-cresol	sediment		0,0996	
128-37-0	(freshwater)		mg/kg	
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (marine water)		0,00996 mg/kg	
2,6-Di-tert-butyl-p-cresol	Soil		0,04769	
128-37-0			mg/kg	
2,6-Di-tert-butyl-p-cresol 128-37-0	oral		8,33 mg/kg	
2,6-Di-tert-butyl-p-cresol	aqua	0,00199		
128-37-0	(intermittent	mg/l		
2,6-Di-tert-butyl-p-cresol	releases) Air			no hazard identified
128-37-0	Air			no nazard identified
methacrylic acid 79-41-4	aqua (freshwater)	0,82 mg/l		
methacrylic acid	Freshwater -	0,45 mg/l		
79-41-4	intermittent	3,12 11.8/2		
methacrylic acid	aqua (marine	0,082 mg/l		
79-41-4 methacrylic acid	water)	100 mg/l		
79-41-4	sewage treatment plant	100 mg/1		
	(STP)			
methacrylic acid 79-41-4	sediment (freshwater)		3,09 mg/kg	
methacrylic acid 79-41-4	sediment		0,309	
methacrylic acid	(marine water) Soil		mg/kg 0,137	
79-41-4	Son		mg/kg	
methacrylic acid	Predator		1-19-1-9	no potential for
79-41-4				bioaccumulation
Ethylene dimethacrylate 97-90-5	aqua (freshwater)	0,139 mg/l		
Ethylene dimethacrylate	aqua (marine	0,0139		
97-90-5	water)	mg/l		
Ethylene dimethacrylate	aqua	0,15 mg/l		
97-90-5	(intermittent releases)			
Ethylene dimethacrylate	sewage	57 mg/l		
97-90-5	treatment plant	J / mg/i		
Ethylene dimethacrylate	sediment		1,6 mg/kg	
97-90-5	(freshwater)		1,0 mg/mg	
Ethylene dimethacrylate 97-90-5	sediment (marine water)		0,16 mg/kg	
Ethylene dimethacrylate 97-90-5	Air			no hazard identified
Ethylene dimethacrylate 97-90-5	Soil		0,239 mg/kg	
Ethylene dimethacrylate	Predator			no potential for
97-90-5				bioaccumulation

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 10 of 30

V003.0

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Workers	dermal	Long term exposure - systemic effects		1,04 mg/kg	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	General population	dermal	Long term exposure - systemic effects		0,625 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	inhalation	Long term exposure - systemic effects		0,822 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	dermal	Long term exposure - systemic effects		0,233 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	inhalation	Long term exposure - systemic effects		0,145 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	dermal	Long term exposure - systemic effects		0,0833 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	oral	Long term exposure - systemic effects		0,0833 mg/kg	
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	inhalation	Long term exposure - systemic effects		1,27 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	dermal	Long term exposure - systemic effects		1,8 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	dermal	Long term exposure - systemic effects		0,9 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	inhalation	Long term exposure - systemic effects		0,31 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	oral	Long term exposure - systemic effects		0,18 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	dermal	Long term exposure - local effects			no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	dermal	Acute/short term exposure - local effects			no potential for bioaccumulation
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	inhalation	Long term exposure - systemic effects		7,4 mg/m3	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	dermal	Long term exposure - systemic effects		2,1 mg/kg	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	dermal	Long term exposure -		0,5 mg/kg	no hazard identified

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 11 of 30

V003.0

			systemic effects		
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	inhalation	Long term exposure - systemic effects	0,86 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	dermal	Long term exposure - systemic effects	0,25 mg/kg	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	oral	Long term exposure - systemic effects	0,25 mg/kg	no hazard identified
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects	88 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects	29,6 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects	4,25 mg/kg	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects	6,55 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects	6,3 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects	2,55 mg/kg	no potential for bioaccumulation
Ethylene dimethacrylate 97-90-5	Workers	inhalation	Long term exposure - systemic effects	2,45 mg/m3	no hazard identified
Ethylene dimethacrylate 97-90-5	Workers	dermal	Long term exposure - systemic effects	1,3 mg/kg	no hazard identified
Ethylene dimethacrylate 97-90-5	General population	inhalation	Long term exposure - systemic effects 1,45 mg/m3		no hazard identified
Ethylene dimethacrylate 97-90-5	General population	dermal	Long term exposure - systemic effects	0,83 mg/kg	no hazard identified
Ethylene dimethacrylate 97-90-5	General population	oral	Long term exposure - systemic effects	0,83 mg/kg	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 12 of 30

V003.0

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid
Colour black
Odor acrylic
Physical state liquid

Melting point

Not applicable, Product is a liquid
Initial boiling point

Currently under determination
Flammability

The product is not flammable.

Explosive limits Not applicable, The product is not flammable.

Flash point $> 93 \,^{\circ}\text{C} (> 199.4 \,^{\circ}\text{F})$

Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature

Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use

Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) Currently under determination Solubility (qualitative) Currently under determination

Partition coefficient: n-octanol/water Not applicable

Mixture

Vapour pressure Currently under determination

Density 1,1 g/cm3 no method / method unknown

(20 °C (68 °F))

pН

Relative vapour density: Currently under determination

Particle characteristics Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 13 of 30

V003.0

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants. Strong bases.

Acids.

Reducing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
2-Hydroxyethyl methacrylate 868-77-9	LD50	5.564 mg/kg	rat	FDA Guideline
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Isobornyl methacrylate 7534-94-3	LD50	3.160 mg/kg	rat	not specified
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	3.125 mg/kg	rat	equivalent or similar to OECD Guideline 423 (Acute Oral toxicity)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	5.564 mg/kg	rat	FDA Guideline
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Butyl hydroxytoluene 128-37-0	LD50	> 6.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methacrylic acid 79-41-4	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Ethylene dimethacrylate 97-90-5	LD50	8.700 mg/kg	rat	FDA Guideline

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 14 of 30

V003.0

Acute dermal toxicity:

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rabbit	not specified
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isobornyl methacrylate 7534-94-3	LD50	> 3.000 mg/kg	rabbit	not specified
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	> 3.170 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Acute toxicity estimate (ATE)	3.171 mg/kg		Expert judgement
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	> 5.000 mg/kg	rabbit	not specified
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Butyl hydroxytoluene 128-37-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
Ethylene dimethacrylate 97-90-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ethylene dimethacrylate 97-90-5	Acute toxicity estimate (ATE)	> 5.000 mg/kg		Expert judgement

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 15 of 30

V003.0

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
methacrylic acid	LC50	3,19 - 6,5 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD
79-41-4						Guideline 403 (Acute
						Inhalation Toxicity)
methacrylic acid	Acute	3,19 mg/l	dust/mist			Expert judgement
79-41-4	toxicity					
	estimate					
	(ATE)					

Skin corrosion/irritation:

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
2-Hydroxyethyl methacrylate 868-77-9	slightly irritating	24 h	rabbit	Draize Test
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isobornyl methacrylate 7534-94-3	mildly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating	24 h	rabbit	not specified
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	not irritating	24 h	rabbit	Draize Test
Triacrylate ester 52408-84-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Ethylene dimethacrylate 97-90-5	not irritating	24 h	rabbit	FDA Guideline

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 16 of 30

V003.0

Serious eye damage/irritation:

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
2-Hydroxyethyl	Category 2B		rabbit	Draize Test
methacrylate	(mildly			
868-77-9	irritating to			
	eyes)			
7,7,9(or 7,9,9)-trimethyl-	not irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
4,13-dioxo-3,14-dioxa-	_			
5,12-diazahexadecane-				
1,16-diyl bismethacrylate				
72869-86-4				
Isobornyl methacrylate	not irritating		rabbit	FDA Guideline
7534-94-3				
Isobornyl methacrylate	slightly		rabbit	Draize Test
7534-94-3	irritating			
Diphenyl-2,4,6-	not irritating		rabbit	not specified
trimethylbenzoyl	_			
phosphine oxide				
75980-60-8				
Reaction mass of	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
pentamethyl-4-	_			Irritation / Corrosion)
piperidylsebacates				·
1065336-91-5				
2-Propenoic acid, 2-	irritating		rabbit	Draize Test
methyl-, 2-(2-				
hydroxyethoxy)ethyl ester				
2351-43-1				
Triacrylate ester	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
52408-84-1	_			
Butyl hydroxytoluene	not irritating		rabbit	Draize Test
128-37-0				
methacrylic acid	corrosive		rabbit	Draize Test
79-41-4				
Ethylene dimethacrylate	not irritating		rabbit	Draize Test
97-90-5				

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 17 of 30

V003.0

Respiratory or skin sensitization:

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
2-Hydroxyethyl methacrylate 868-77-9	not sensitising	Buehler test	guinea pig	Buehler test
2-Hydroxyethyl methacrylate 868-77-9	sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isobornyl methacrylate 7534-94-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Sub-Category 1A (sensitising)	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Triacrylate ester 52408-84-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Butyl hydroxytoluene 128-37-0	not sensitising	Draize Test	guinea pig	Draize Test
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Ethylene dimethacrylate 97-90-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

LOCTITE 3D PRO476 Black Page 18 of 30

V003.0

SDS No.: 693565

Germ cell mutagenicity:

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl methacrylate 7534-94-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl methacrylate 7534-94-3	negative	Times testy	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl methacrylate 7534-94-3	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Triacrylate ester 52408-84-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Triacrylate ester 52408-84-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Triacrylate ester 52408-84-1	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butyl hydroxytoluene 128-37-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	in vitro mammalian chromosome aberration test	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	mammalian cell gene mutation assay	with		not specified
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethylene dimethacrylate 97-90-5	positive	in vitro mammalian chromosome aberration test	without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		Drosophila melanogaster	not specified
Triacrylate ester 52408-84-1	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Butyl hydroxytoluene 128-37-0	negative	oral: feed		rat	not specified
methacrylic acid 79-41-4	negative	inhalation		mouse	equivalent or similar to OECD Guideline 478 (Genetic

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 19 of 30

V003.0

				Toxicology: Rodent Dominant Lethal Test)
methacrylic acid 79-41-4	negative	oral: gavage	mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Ethylene dimethacrylate 97-90-5	negative	oral: unspecified	mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Butyl hydroxytoluene 128-37-0		oral: feed	2 y daily	rat	male	
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Ethylene dimethacrylate 97-90-5		inhalation	2 years 6 hours/day, 5 days/week	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 20 of 30

V003.0

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	screening	oral: gavage	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study)
Isobornyl methacrylate 7534-94-3	NOAEL P 25 mg/kg NOAEL F1 500 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	NOAEL P < 221 mg/kg NOAEL F1 221 mg/kg		oral: feed	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Triacrylate ester 52408-84-1	NOAEL P 750 mg/kg NOAEL F1 >= 750 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL P 500 mg/kg	Two generation study	oral: feed	rat	not specified
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Ethylene dimethacrylate 97-90-5	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg		oral: gavage	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study)

STOT-single exposure:

Hazardous substances	Assessment	Route of	Target Organs	Remarks
CAS-No.		exposure		
methacrylic acid 79-41-4	May cause respiratory irritation.			
Ethylene dimethacrylate 97-90-5	May cause respiratory irritation.			

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 21 of 30

V003.0

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 100 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	NOAEL 100 mg/kg	oral: gavage	3 m 5 d/w	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Triacrylate ester 52408-84-1	NOAEL 250 mg/kg	oral: gavage	28-52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL 25 mg/kg	oral: feed	daily	rat	not specified
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Ethylene dimethacrylate 97-90-5	NOAEL 100 mg/kg	oral: gavage	49 d once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 22 of 30

V003.0

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate 868-77-9	LC50	> 100 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	LC50	10,1 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl methacrylate 7534-94-3	LC50	1,79 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LC50	1,4 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LC50	0,9 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Triacrylate ester 52408-84-1	LC50	5,74 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butyl hydroxytoluene 128-37-0	LC50	Toxicity > Water solubility	96 h	Brachydanio rerio (new name: Danio rerio)	EU Method C.1 (Acute Toxicity for Fish)
Butyl hydroxytoluene 128-37-0	NOEC	0,053 mg/l	30 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)
methacrylic acid 79-41-4	LC50	85 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
methacrylic acid 79-41-4	NOEC	10 mg/l	35 d	Danio rerio	OECD Guideline 210 (fish early lite stage toxicity test)
Ethylene dimethacrylate 97-90-5	LC50	15,95 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	EC50	> 1,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl methacrylate 7534-94-3	EC50	> 2,57 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	3,53 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triacrylate ester	EC50	91,4 mg/l	48 h	Daphnia magna	OECD Guideline 202

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 23 of 30

V003.0

52408-84-1					(Daphnia sp. Acute Immobilisation Test)
Butyl hydroxytoluene 128-37-0	EC50	0,48 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Ethylene dimethacrylate 97-90-5	EC50	44,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate	NOEC	24,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
868-77-9		Ŭ		1	magna, Reproduction Test)
Isobornyl methacrylate	NOEC	0,233 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
7534-94-3					magna, Reproduction Test)
Reaction mass of pentamethyl-	NOEC	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
4-piperidylsebacates				1 0	magna, Reproduction Test)
1065336-91-5					
Butyl hydroxytoluene	NOEC	0,069 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
128-37-0					magna, Reproduction Test)
methacrylic acid	NOEC	53 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
79-41-4					magna, Reproduction Test)
Ethylene dimethacrylate	NOEC	5,05 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
97-90-5		=			magna, Reproduction Test)

Toxicity (Algae):

LOCTITE 3D PRO476 Black Page 24 of 30

V003.0

SDS No.: 693565

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	,
2-Hydroxyethyl methacrylate 868-77-9	NOEC	400 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	NOEC	0,21 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl methacrylate 7534-94-3	EC50	2,66 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl methacrylate 7534-94-3	NOEC	0,254 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 2,01 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC10	1,56 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	NOEC	0,22 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	EC50	1,68 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC50	12,2 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC10	2,06 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Butyl hydroxytoluene 128-37-0	EC10	0,4 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethylene dimethacrylate 97-90-5	EC50	17,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethylene dimethacrylate 97-90-5	EC10	6,93 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate 868-77-9	EC0	> 3.000 mg/l	16 h	Pseudomonas fluorescens	other guideline:
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC 50	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates	IC50	100 mg/l	3 h		OECD Guideline 209 (Activated Sludge,

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 25 of 30

V003.0

1065336-91-5					Respiration Inhibition Test)
Triacrylate ester	EC20	507 mg/l	3 h	activated sludge	OECD Guideline 209
52408-84-1					(Activated Sludge,
					Respiration Inhibition Test)
Butyl hydroxytoluene	EC50	Toxicity > Water	3 h	activated sludge	OECD Guideline 209
128-37-0		solubility			(Activated Sludge,
					Respiration Inhibition Test)
methacrylic acid	EC10	100 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8
79-41-4					(Pseudomonas
					Zellvermehrungshemm-
					Test)
Ethylene dimethacrylate	EC50	570 mg/l	3 h	activated sludge of a	ISO 8192 (Test for
97-90-5				predominantly domestic sewage	Inhibition of Oxygen
					Consumption by Activated
					Sludge)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	not readily biodegradable.	aerobic	22 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isobornyl methacrylate 7534-94-3	readily biodegradable	aerobic	70 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not readily biodegradable.	aerobic	0 - 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	not readily biodegradable.	aerobic	38 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester 2351-43-1	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Triacrylate ester 52408-84-1	readily biodegradable	aerobic	72 - 85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Butyl hydroxytoluene 128-37-0	not readily biodegradable.	aerobic	4,5 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Butyl hydroxytoluene 128-37-0	not inherently biodegradable	aerobic	5,2 - 5,6 %	35 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Ethylene dimethacrylate 97-90-5	not readily biodegradable.	aerobic	69 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

${\bf 12.3.\ Bioaccumulative\ potential}$

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 26 of 30

V003.0

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Isobornyl methacrylate 7534-94-3	37	56 day	24 °C	Danio rerio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	< 31,4	56 d	24,5 °C	Cyprinus carpio	other guideline:
Butyl hydroxytoluene 128-37-0	330 - 1.800	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 27 of 30

V003.0

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
2-Hydroxyethyl methacrylate	0,42	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
868-77-9			Flask Method)
7,7,9(or 7,9,9)-trimethyl-4,13-	3,39	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
dioxo-3,14-dioxa-5,12-			Method)
diazahexadecane-1,16-diyl			
bismethacrylate			
72869-86-4			
Isobornyl methacrylate	5,09		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
7534-94-3			Method)
Diphenyl-2,4,6-	3,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
trimethylbenzoyl phosphine			Method)
oxide			
75980-60-8			
Reaction mass of	> 2,37 - 2,77	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
pentamethyl-4-			Flask Method)
piperidylsebacates			
1065336-91-5			
Butyl hydroxytoluene	5,1		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
128-37-0			Flask Method)
methacrylic acid	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
79-41-4			Flask Method)
Ethylene dimethacrylate	2,4		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
97-90-5			Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
2-Hydroxyethyl methacrylate 868-77-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobornyl methacrylate 7534-94-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Triacrylate ester 52408-84-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butyl hydroxytoluene 128-37-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
methacrylic acid 79-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethylene dimethacrylate 97-90-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

LOCTITE 3D PRO476 Black Page 28 of 30

V003.0

SDS No.: 693565

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction
	mass of pentamethyl-4-piperidylsebacates, Urethane dimethacrylate)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction

mass of pentamethyl-4-piperidylsebacates, Urethane dimethacrylate)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction

mass of pentamethyl-4-piperidylsebacates, Urethane dimethacrylate)
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of pentamethyl-4-piperidylsebacates, Urethane dimethacrylate)

IATA Environmentally hazardous substance, liquid, n.o.s. (Reaction mass of pentamethyl-4-

piperidylsebacates, Urethane dimethacrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	Q

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 29 of 30

V003.0

ADN Environmentally Hazardous

IMDG Marine Pollutant

IATA Environmentally Hazardous

14.6. Special precautions for user

ADR not applicable
Tunnelcode:
RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SDS No.: 693565 LOCTITE 3D PRO476 Black Page 30 of 30

V003.0

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

EU EXPLD 1:

Substance with a Union workplace exposure limit

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.